



## CR 3

قطر دهانه خروجی mm	قطر دهانه ورودی mm	حداکثر دبی (متر مکعب در ساعت)	حداقل هد (متر)	حداکثر هد (متر)	شدت جریان	توان موتور P <sub>r</sub> HP	توان موتور P <sub>r</sub> KW	RPM	ولتاژ و فاز	مدل	ردیف
1"/1¼"	1"/1¼"	1.2 - 4.46	23	60	1/9	1	0/75	2870	3×380-415Y	CR 3-9	2
1"/1¼"	1"/1¼"	1.2 - 4.5	28/33	73/17	2/5	1/5	1/1	2870	3×380-415Y	CR 3-11	3
1"/1¼"	1"/1¼"	1.2 - 4.47	30	80	2/5	1/5	1/1	2870	3×380-415Y	CR 3-12	4
1"/1¼"	1"/1¼"	1.2- 4.46	33/14	86/28	2/5	1/5	1/1	2870	3×380-415Y	CR 3-13	5
1"/1¼"	1"/1¼"	1.2- 4.44	37/18	99	2/5	1/5	1/1	2870	3×380-415Y	CR 3-15	6
1"/1¼"	1"/1¼"	1.2-4.52	44/23	113/7	3/15	2	1/5	2970	3×380-415Y	CR 3-17	7
1"/1¼"	1"/1¼"	1.2-4.51	44/33	126/7	3/15	2	1/5	2910	3×380-415Y	CR 3-19	8
1"/1¼"	1"/1¼"	1.2-4.54	55/95	140	4/45	3	2/2	2910	3×380-415Y	CR 3-21	9
1"/1¼"	1"/1¼"	1.2-4.53	60	154	4/45	3	2.2	2910	3×380-415Y	CR 3-23	10
1"/1¼"	1"/1¼"	1.2-4.51	67/08	167/1	4/45	3	2/2	2910	3×380-415Y	CR 3-25	11

۰۲۱-۸۸۸۳۰۰۳۱

۰۲۱-۸۸۸۳۰۰۳۲



## CR 5

GRUNDFOS 

قطر دهانه خروجی mm	قطر دهانه ورودی mm	حداکثر دبی (متر مکعب در ساعت)	حداقل هد (متر)	حداکثر هد (متر)	شدت جریان	توان موتور Pr HP	توان موتور Pr KW	RPM	ولتاژ و فاز	مدل	ردیف
1"/1¼"	1"/1¼"	2.5-8.43	20/99	48/76	2/5	1/5	1/1	2870	3×380-415Y	CR 5-7	2
1"/1¼"	1"/1¼"	2.5-8.35	23/54	55/43	2/5	1/5	1/1	2870	3×380-415Y	CR 5-8	3
1"/1¼"	1"/1¼"	2.5-8.55	27/37	63	3/15	2	1/5	2910	3×380-415Y	CR 5-9	4
1"/1¼"	1"/1¼"	2.5-8.53	30	70	3/15	2	1/5	2910	3×380-415Y	CR 5-10	5
1"/1¼"	1"/1¼"	2.5-8.58	34/25	77/17	4/45	3	2/2	2910	3×380-415Y	CR 5-11	6
1"/1¼"	1"/1¼"	2.5-8.56	37/67	83/91	4/45	3	2/2	2910	3×380-415Y	CR 5-12	7
1"/1¼"	1"/1¼"	2.5-8.57	40	90/88	4/45	3	2/2	2910	3×380-415Y	CR 5-13	8
1"/1¼"	1"/1¼"	2.5-8.49	44/68	97/64	4/45	3	2/2	2910	3×380-415Y	CR 5-14	9
1"/1¼"	1"/1¼"	2.5-8.47	47/95	104/4	4/45	3	2/2	2910	3×380-415Y	CR 5-15	10
1"/1¼"	1"/1¼"	2.5-8.52	50	111/4	4/45	3	2/2	2910	3×380-415Y	CR 5-16	11
1"/1¼"	1"/1¼"	2.5-8.54	57/91	125/8	6/3	4	3	2920	3×380-415D	CR 5-18	12
1"/1¼"	1"/1¼"	2.5-8.49	64/63	140	6/3	4	3	2920	3×380-415D	CR 5-20	13
1"/1¼"	1"/1¼"	2.5-8.61	71/88	154/4	7/9	5/5	4	2940	3×380-415D	CR 5-22	14
1"/1¼"	1"/1¼"	2.5-8.61	80	168/1	7/9	5/5	4	2940	3×380-415D	CR 5-24	15
1"/1¼"	1"/1¼"	2.5-8.56	85/46	182/3	7/9	5/5	4	2940	3×380-415D	CR 5-26	16
1"/1¼"	1"/1¼"	2.5-8.56	94/63	203	7/9	5/5	4	2940	3×380-415D	CR 5-29	17
1"/1¼"	1"/1¼"	2.5-8.53	106/8	224/7	11	7/5	5/5	2940	3×380-415D	CR 5-32	18

• ۲۱-۸۸۸۳۰۰۳۱

• ۲۱-۸۸۸۳۰۰۳۲



## CR 10

ردیف	مدل	ولتاژ و فاز	RPM	توان موتور P <sub>۲</sub> HP	توان موتور P <sub>۲</sub> KW	شدت جریان	حداکثر هد (متر)	حداقل هد (متر)	حداکثر دبی (متر مکعب در ساعت)	قطر دهانه ورودی mm	قطر دهانه خروجی mm
1	CR 10-4	3×380-415Y	2910	2	1/5	3/15	40/91	22/32	5-13.1	1½"	1½"
2	CR 10-5	3×380-415Y	2910	3	2/2	4/45	51/36	28/83	5-13.1	1½"	1½"
3	CR 10-6	3×380-415Y	2910	3	2/2	4/45	61/52	34/83	5-13.1	1½"	1½"
4	CR 10-7	3×380-415D	2920	4	3	6/3	71/92	40	5-13.1	1½"	1½"
5	CR 10-8	3×380-415D	2920	4	3	6/3	81/99	46/44	5-13.1	1½"	1½"
6	CR 10-9	3×380-415D	2920	4	3	6/3	92	52/09	5-13.1	1½"	1½"
7	CR 10-10	3×380-415D	2940	5/5	4	7/9	102/8	59/76	5-13.1	1½"	1½"
8	CR 10-12	3×380-415D	2940	5/5	4	7/9	123/3	70	5-13.1	1½"	1½"
9	CR 10-14	3×380-415D	2940	5/5	5/5	11	144	83/21	5-13.1	1½"	1½"
10	CR 10-16	3×380-415D	2940	5/5	5/5	11	164/3	93/77	5-13.1	1½"	1½"
11	CR 10-18	3×380-415D	2920	7/5	10	14.4-14	185/5	106/2	5-13.1	1½"	1½"
12	CR 10-20	3×380-415D	2920	7/5	10	14.4-14	206	120	5-13.1	1½"	1½"
13	CR 10-22	3×380-415D	2920	7/5	10	14.4-14	226/4	129/6	5-13.1	1½"	1½"

۰۲۱-۸۸۸۳۰۰۳۱

۰۲۱-۸۸۸۳۰۰۳۲



## CR 20

GRUNDFOS 

قطر دهانه خروجی mm	قطر دهانه ورودی mm	حداکثر دبی (متر مکعب در ساعت)	حداقل هد (متر)	حداکثر هد (متر)	شدت جریان	توان موتور P <sub>۲</sub> HP	توان موتور P <sub>۲</sub> KW	RPM	ولتاژ و فاز	مدل	ردیف
2"	2"	10.7-29.4	28/89	58/8	11	7/5	5/5	2940	3×380-415D	CR 20-4	1
2"	2"	10.7-29.4	35	73/35	11	7/5	5/5	2940	3×380-415D	CR 20-5	2
2"	2"	10.7-29.4	45	88/94	14.4-14	10	7/5	2920	3×380-415D	CR 20-6	3
2"	2"	10.7-29.4	52/47	104	14.4-14	10	7/5	2920	3×380-415D	CR 20-7	4
2"	2"	10.8-29.4	60	120	20.8-19.8	15	11	2950	3×380-415D	CR 20-8	5
2"	2"	10.8-29.4	78/22	148/9	20.8-19.8	15	11	2950	3×380-415D	CR 20-10	6
2"	2"	10.8-29.4	92	178/7	28-26	20	15	2950	3×380-415D	CR 20-12	7
2"	2"	10.8-29.4	107/6	208	28-26	20	15	2950	3×380-415D	CR 20-14	8
2"	2"	10.8-29.4	130/8	251/6	34.5-32.5	25	18/5	2950	3×380-415D	CR 20-17	9

۰۲۱-۸۸۸۳۰۰۳۱

۰۲۱-۸۸۸۳۰۰۳۲



## CR 32

قطر دهانه خروجی mm	قطر دهانه ورودی mm	حداکثر دبی (متر مکعب در ساعت)	حداقل هد (متر)	حداکثر هد (متر)	شدت جریان	توان موتور P <sub>۲</sub> HP	توان موتور P <sub>۲</sub> KW	RPM	ولتاژ و فاز	مدل	ردیف
2½ "	2½ "	15.3-40.5	18/28	39/6	7/9	5/5	4	2940	3×380-415D	CR 32-2	1
2½ "	2½ "	15.3-40.5	30	59/16	11	7/5	5/5	2940	3×380-415D	CR 32-3	2
2½ "	2½ "	15.3-40.5	40	78/6	14.4-14	10	7/5	2920	3×380-415D	CR 32-4	3
2½ "	2½ "	15.3-40.5	50	100	20.8-19.8	15	11	2950	3×380-415D	CR 32-5	4
2½ "	2½ "	15.3-40.5	62/8	118	20.8-19.8	15	11	2950	3×380-415D	CR 32-6	5
2½ "	2½ "	15.3-40.5	70/9	138/2	28-26	20	15	2950	3×380-415D	CR 32-7	6
2½ "	2½ "	15.3-40.5	80	158/3	28-26	20	15	2950	3×380-415D	CR 32-8	7
2½ "	2½ "	15.3-40.5	104/6	196/6	34.5-32.5	25	18/5	2950	3×380-415D	CR 32-10	8
2½ "	2½ "	15.3-40.5	115/9	217	39/5	30	22	2950	3×380-415D	CR 32-11	9
2½ "	2½ "	15.3-40.5	127/2	235/7	39/5	30	22	2950	3×380-415D	CR 32-12	10

۰۲۱-۸۸۸۳۰۰۳۱

۰۲۱-۸۸۸۳۰۰۳۲